







Other specifications:

Quick and easy changeover for different caps

Adjustable rotation speed

Linear mechanism with continuous capping (non-stop operation)

Equipped with 8 polyurethane capping heads with adjustable rotation to prevent cap damage

Side anti-wear belt for bottle holding, adjustable in height and width for various bottle sizes

No part replacement required for different cap types

Adjustable height for different bottles

3 m stainless steel conveyor



Options:

In industries:

Cap sorting and feeding system for standard caps
GMP-grade enclosure

Suitable for detergent, chemical, pharmaceutical, cosmetic & personal care, food and beverage containers



Feature	Specifications
capping speed	2,000 – 5,000 caps per hour
bottle width	30 - 100 mm
bottle height	80 - 300 mm
cap type	flat, pump, trigger caps and jars
bottle material	plastic
frame and covering	Epoxy-coated Iron with SST 304 Covering
power supply	AC380V/110V 3PH 50/60HZ
machine dimensions	300 cm (L) × 80 cm (W) × 220 cm (H)



- Address: No. 10, Sanat Street, Zaghros Street, Zaghros Industrial Town, Shahr-e Qods, Tehran, 3754181190, Iran
- Phone: 02146801050 02146801060 09120550895
- Website: radanmachine.com
- Email: radanmachine@gmail.com